CM-WC2063

DIESEL GENERATOR SET / OPEN + SILENT

OPEN SET

SILENT SET

2,063 kVA	1,875 kVA	50 Hz	400/230 V
STANDBY POWER	PRIME POWER	FREQUENCY	VOLTAGE

Weichai 16M33D1800E310

3 phase · 0.8 PF · 1500 rpm

Configuration	Typical application
Open (skid-mounted)	**Plant rooms, container frames, OEM builds**
Silent (acoustic canopy)	**Approx. 75 dB(A) at 7 m, weatherproof**
Containerised	**ISO footprint, walk-in or standard, up to 45 ft**

Enclosure dimensions, weights and tank size are issued with the quotation.

GENERAL CHARACTERISTICS

CM-WC2063 · 50 Hz · 3 Phase

RATED PERFORMANCE

Standby Power (kVA)	**2,063**
Standby Power (kW)	**1,650**
Prime Power (kVA)	**1,875**
Prime Power (kW)	**1,500**
Power Factor (Cos Phi)	**0.8**
Diesel Engine	**16M33D1800E310**
Frequency (Hz)	**50**
Rated Speed (rpm)	**1500**
Phase	**3**
Standard Voltage (V)	**400/230**

POWER DEFINITIONS

STANDBY POWER (ESP)

Available for supplying emergency power during a utility interruption. The stated rating follows ISO 8528-1; overload is not permitted.

PRIME POWER (PRP)

Available for an unlimited number of annual operating hours in variable-load applications, in accordance with ISO 8528-1.

TERMS OF USE

Nominal power is stated at 25 °C inlet-air temperature, 100 kPa barometric pressure (100 m A.S.L.) and 30% relative humidity.

RATED OUTPUT CURRENT BY VOLTAGE

Rated voltage	Standby current (2,063 kVA)	Prime current (1,875 kVA)
400/230 V	**2977.7 A**	**2706.3 A**
380/220 V	**3134.4 A**	**2848.8 A**
415/240 V	**2870.1 A**	**2608.5 A**